




BEARING USA CORP.

22,225 mm x 50,8 mm x 14,26 mm NTN
4T-07087X/07210X tapered roller bearings



Bearing No. 4T-07087X/07210X

| | |
|---------------------------------|-----------------------|
| Size | 22.225x50.8x15.011 mm |
| Bore Diameter | 22,225 mm |
| Outer Diameter | 50,8 mm |
| Width | 15,011 mm |
| d | 22,225 mm |
| D | 50,8 mm |
| T | 15,011 mm |
| B | 14,26 mm |
| C | 12,7 mm |
| a | 18 mm |
| rs min | 1.5 mm |
| r1s min | 1.5 mm |
| e | 0.4 |
| Y2 | 1.49 |
| Y0 | 0.82 |
| Mass | 0.14 kg |
| Dynamic load, C | 26 kN |
| Rating life coefficient, A2 | 1.4 |
| Static load, C0 | 28 kN |
| Nlim (oil) | 10,000 rpm |
| Nlim (grease) | 7,500 rpm |
| Min operating temperature, Tmin | -40 ° C |
| Max operating temperature, Tmax | 120 ° C |
| ra max | 1.5 mm |

4T-07087X/07210X Bearing 2D drawings and 3D CAD models



BEARING USA CORP.

r1a max

1.5 mm